

ISHIKAWAJIMA-SHIBAURA MACHINERY CO., LTD.

EXECUTIVE ORDER U-R-026-0096 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

| MODEL YEAR | ENGINE FAMILY | DISPLACEMENT (liters) | FUEL TYPE | USEFUL LIFE (hours) | | |
|---|---------------|-------------------------------|-----------|------------------------|--|--|
| 2004 | 4H3XL1.13LCS | 1.131 | Diesel | 3000 | | |
| SPECIAL FEATURES & EMISSION CONTROL SYSTEMS | | TYPICAL EQUIPMENT APPLICATION | | | | |
| Indirect Diesel Injection | | | Generator | | | |

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

| RATED POWER | EMISSION STANDARD | | EXHAUST (g/kw-hr) | | | | OPACITY (%) | | | |
|---------------------|----------------------|------|-------------------|-----|----------|-----|-------------|-------|------|------|
| CLASS | CATEGORY | | HC | NOx | NMHC+NOx | CO | PM | ACCEL | LUG | PEAK |
| 8 <u><</u> KW<19 | Tier 1 | STD | N/A | N/A | 9.5 | 6.6 | 0.80 | N/A | N/A | |
| | | CERT | | | 4.4 | 2.1 | 0.25 | 14/7 | IN/A | N/A |

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this _____ day of January 2004.

Allen yons, Chief

Mobile Source Operations Division

ATTACHMENT 1 OF1

Engine Model Summary Form

Ishikawajima-Shibaura Machinery Co., Ltd.

Manufacturer:

Engine category: Nonroad Cl
EPA Engine Family: 4H3XL1.13LCS

Mfr Family Name: N/A

W-R-026-0096

New Submission Process Code:

| n Control SAE J193(| | STATE OF THE PARTY |
|--|--|--|
| 9.Emisslon Control Device Per SAE J193 | | Control of the same of the control |
| 8.Fuel Rate: 9.Emisston Control (lbs/hr)@peak torque Device Per SAE J193(| 247.1.4 5.54/-0.4 N/A N/A N/A N/A N/A N/A N/A N/A N/A IFI 147-2.3 7.14/-0.5 N/A | CONTRACTOR OF THE PROPERTY OF |
| 7.Fuel Rate: mm/stroke@peak torque | NA NA NA | THE RESERVE AND THE PROPERTY OF THE PARTY OF |
| 6.Torque @ RPM (SEA Gross) | N/A N/A N/A | |
| 5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only) | 5.5+/-0.4 7.1+/-0.7 | |
| 4.Fuel Rate: mm/stroke @ peak HP (for diesel only) | 403G-11 HH13/1500C 12.7@1500 22.2+/-1.4 5.5+/-0.4 N/A N/A N/A N/A N/A IFI H H16/1800C 15.8@1800 24.1+/-2.3 7.1+/-0.7 N/A N/A N/A N/A N/A IFI N/A IFI N/A | |
| 3.BHP@RPM (SAE Gross) | 12.7@1500 15.8@1800 15.0@1800 | |
| 1.Engine Code 2.Engine Model | 403G-11 HH13/1500C 12.7@1500 22.2 403C-11 HH16/1800C 15.8@1800 24.1 # S773LG 15/1800C 15.0@1800 24.1 | |
| 1.Engine Code | 403G-11 403C-11 \$773L | |